





















## technical information

			Tiles	Rolls	Kult	Klic hydro sound
		<b>wear layer</b>	80/20 PVC Glass			
		<b>finish</b>	PVC Glass fibre reinforced	PVC Glass fibre reinforced	PVC Glass fibre reinforced	Hard PVC
	ISO 1765	<b>total thickness</b>	3,2 mm	2,3 mm	3,2 mm	7,5 mm
	ISO 8543	<b>total weight</b>	4.500 g/m <sup>2</sup>	2.500 g/m <sup>2</sup>	4.500 g/m <sup>2</sup>	7.700 g/m <sup>2</sup>
	EN 1307	<b>level of use</b>	class 33 heavy commercial public areas			
	EN 986/ ISO 2551	<b>dimensional stability</b>	< 0,1 %	/	< 0,1 %	/
	EN 985	<b>suitability for castor chair</b>	intensive use	intensive use	intensive use	intensive use
	ISO 6356	<b>static loading</b>	< 2KV	< 2KV	< 2KV	< 2KV
	EN13893	<b>slip resistance</b>	> 0,3	> 0,3	> 0,3	> 0,3
	EN ISO 10140-3	<b>impact sound ΔLw</b>	14 dB	12 dB	14 dB	22 dB
	EPLF 021029-2	<b>Drum sound absorption</b>	40%	39%	40%	40%
	EN ISO 354	<b>sound absorption αS</b>	200 Hz: 0,01 2000Hz: 0,09	200 Hz: 0,01 2000Hz: 0,09	200 Hz: 0,01 2000Hz: 0,09	200 Hz: 0,01 2000Hz: 0,09
	EN 105-B02	<b>Light fastness</b>	≥ 7	≥ 7	≥ 7	≥ 7
	EN 13501-1	<b>reaction to fire</b>	B <sub>f1</sub> -s1	B <sub>f1</sub> -s1	B <sub>f1</sub> -s1	B <sub>f1</sub> -s1
	EN 994	<b>tile size</b>	500 x 500 mm	/	on request	915 x 305 mm
	ISO 24341	<b>width</b>	/	200 – 202 cm	/	/
	ISO 24341	<b>length</b>	/	on request	/	/
	ISO 24334	<b>locking strength</b>	/	/	/	fulfills the requirements for class 33
	EN 1814	<b>resistance to fraying</b>	pass	pass	pass	pass
	EN ISO 26987	<b>staining resistance</b>	extremely good	extremely good	extremely good	extremely good
	EN 1307	<b>suitability for humid conditions</b>	/	suitable	/	suitable
	EN 14041	<b>Dop nr.</b>	0493-CPR-0110	0493-CPR-0111	0493-CPR-0110	0493-CPR-0115

Ntgrate® meets all of the product required CE standards.

This information is for informational purposes only and does not constitute any obligation on our part. Ntgrate® reserves the right to change materials, dimensions and characteristics without prior notice. Ntgrate® cannot be held responsible for any differences between the pictures or descriptions and the actual product. Please note that actual colors may vary from what is shown in this catalog. All photos are the sole property of Ntgrate®.

**ntgrate®**