Product description Scheucher Holzindustrie GmbH





Product Multilayer parquet flooring for fully glued down installations on standard-conforming subfloors

manufactured according to EN 13489 "Multilayer parquet"

Dimension 700 x 140 x 9.8mm, 14 Strips/Pack = 1.372m², 42 Packs/Pallet = 57.624m²

Top layer 1-strip plank from selected hardwood with a wear layer of approx. 3.6 mm ± 10%

Base layer Water-resistant glued plywood birch from Central European production **Moisture content** delivered with a moisture content of 7 % +/- 2 %. according to EN 13489

Gluing 100% formaldehyde-free RPU bonding

Surface RAW SURFACE: sanded, raw wood surface

TENSEO: UV-coatings from Bona, Sweden. Our UV-coatings are solvent-free as well as emission-free, have a solid content of 100% and an anti-scratch-coating to avoid fine scratches in the lacquer. They are adjusted that hard elastic so that light dents in the wood do not lead to a breakage of the lacquer. The closed-pore antistatic varnish guarantees lowest soiling as well as

resistant glue

easy cleaning without additional additives!

SEDA: Scheucher oils and waxes are based on natural resources and are fully oxidative drying,

not film-forming and partially repairable.

Weight approx. 7 kg/m²

Fire prot. class C_{fl} -s1 at glue-down installation

Underfl. heating suitable, $R_T = 0.058 \text{ m}^2\text{K/W}$


Fields of use Floors and walls, living and object area (meet the highest class C according to. ÖN C2354)

Product description Scheucher Holzindustrie GmbH



Room climate

Room temperature should be kept at a constant of 18–24°C and the relative humidity between 30% und 65%! This generally requires an appropriate air humidification in the heating season. We therefor recommend cold humidifiers with an integrated sterilization system. The installation of a Fidbox records your climate above and under your parquet floor, reports deviations from the optimum climate and can be conveniently monitored by mobile app.



Installation

fully glued down with a classic Tongue/Groove-connection


Installation patterns:




Herringbone




Irregular pattern




Brick pattern



Cube



Parallel pattern



Ladder pattern

Example in Oak Natur Natura

