

SPECIFICATIONS dimensions and characteristics of our collections:

GAMME NATURE - PLANCHER D'AUTREFOIS - CHENE SCIE

PRIVILEGE CAFE - VIEUX DE FRANCE - LOFT - PLANCHER DES ILES - PARQUET WELLNESS - GAMME EXTREME (Variable dimensions according to the collections)

**Solid plankflooring French oak 14 mm**



**Thickness:** 14 mm (+/- for the sawed oak)

**Widths:** (variable according to the collection) 70 / 90 / 110 / 130 / 150 mm

**Lengths:** width 70 : 400 to 700 mm, with microbevels on all 4 edges MGO4, with or without bevel in unfinished (to sand).  
other widths : 400 to 2 000 mm with lightly bevels on all 4 edges PGO4, with or without bevel in unfinished (to sand). Compatible with underfloor heating (low temperature) up to 150 mm wide, refreshing ground not compatible, see data sheet.

**Solid plankflooring French oak 21 or 22 mm**



**Thickness:** 21 mm (+/- for the sawed oak)

**Widths:** (variable according to the collection) 70 / 90 / 110 / 140 / 170 / 190 mm

**Thickness:** 22 mm (+/- for the sawed oak)

**Widths:** (variable according to the collection) 70 / 90 / 110 / 140 mm

**Lengths:** width 70 : 400 to 800 mm, with microbevels on all 4 edges MGO4, with or without bevel in unfinished (to sand). other widths : 400 to 2 000 mm, with lightly bevels on all 4 edges PGO4, with or without bevel in unfinished (to sand).  
with tongue and groove on all four sides

**MULTILAYER PLYWOOD oak XXL, full strip**



**Thickness:** 15 mm (+/- for the sawed oak)

**Widths:** 230 to 350 mm (290 max. in the Sawn Face)

**Lengths:** variables from 2500 to 4 500 mm, be able to go to 5 500 mm

**Top layer:** +/- 5 mm (+/- for the Sawn Face)

**Bevel :** PGO 2 or aged / distressed bevel for the antic line.

**Middle:** oak 5 mm. **On the back :** oak 5 mm

Glued installation. Compatible with underfloor heating (low temperature) in glued installation. see data sheet.

**Choice :** Plancher d'autrefois, Loft, Plancher des îles, Chêne scié, Vieux de France, Privilège café, Parquet Wellness :

special choice with knots, without mastic open knots for the solid plankflooring and sometimes filled for the multilayer

**Gamme nature (Natural oak) :** first choice, rustic (RUA), classic (tradition), confort - **XXL :** big knots and cracks accepted, dark brown filler, little sapwood.

**Note :** Can be delivered in fix or variable widths according to their availability. In case of 2 widths, we need the same number of 1m of each width.

**Chêne scié (Sawed oak) :** Risk of height difference. Thicknesses and top layer with light variations - **Plancher d'autrefois :** aged / distressed bevels.

the technical specifications are susceptible of modifications without advance notice from us.

**MULTILAYER PLYWOOD French oak TOP 4, full strip**



**Thickness:** 15,2 mm (+/- for the sawed oak)

**Widths:** (variable according to the collection) 110 mm (mainly motives for herringbone installation...), 140, 170, 190 et 220\* mm (\*220 consult us limited stock).

**Lengths:** mixed variable from 1000 to 2 200 mm

**Top layer:** +/- 4 mm thick oak (+/- 3,5 mm for the sawed oak),

**Bevel PGO 4 :** lightly bevels +/- 2 mm on all four edges (1,5 mm after sanding), with tongue and groove on all four sides

**Multilayer plywood:** birch

Compatible with underfloor heating (low temperature) up to 190 mm wide, width 220 mm in the course of tries, compatible refreshing ground in 140 mm except choice with sapwood, see data sheet

**MULTILAYER PLYWOOD French oak TOP 6, full strip**



**Thickness:** 20 mm (+/- for the sawed oak)

**Widths:** (variable according to the collection) 140 and 170 (190) mm

**Lengths:** Mixed variables from 1000 to 2 200 mm

**Top layer:** 6 mm (+/- 5,5 to 6 mm for the sawed oak)

**Bevel PGO 4 :** lightly bevels +/- 2 mm on all four edges (1,5 mm after sanding), with tongue and groove on all four sides

**Multilayer plywood:** birch

Compatible with underfloor heating (low temperature) up to 170 mm wide, see data sheet.